

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/001442 A1

(51) International Patent Classification⁷:
H04K 3/00

G01S 7/36,

(74) Agent: FÖRSVARETS MATERIELVERK; Patenten-
heten, S-115 88 Stockholm (SE).

(21) International Application Number:
PCT/SE2003/001042

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 18 June 2003 (18.06.2003)

Swedish

(25) Filing Language: Swedish

Swedish

(26) Publication Language: English

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(30) Priority Data:
0201873-7 19 June 2002 (19.06.2002) SE

Published:


— with international search report

(71) Applicant (for all designated States except US): TOT-
TALFÖRSVARETS FORSKNINGSIINSTITUT
[SE/SE]; S-172 90 Stockholm (SE).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(72) Inventor; and
(75) Inventor/Applicant (for US only): ENEROTH, Anders
[SE/SE]; Örtomta Ringkullavägen 14, S-590 62 Linghem
(SE).

(54) Title: INTERNAL LINK FOR AIRCRAFT



WO 2004/001442 A1

(57) Abstract: The present invention relates to an internal link for aircraft having at least a first pylon which is intended for a load and provided with signal cabling, intended for e.g. countermeasure pods, and power supply, and at least a second pylon which is intended for a load and provided with power supply, but which has no corresponding signal cabling. Signals to the load of the second pylon are sent via the signal cabling to first signal conversion equipment in connection with the first pylon and are sent through an antenna to second signal conversion equipment in connection with the second pylon where it is converted into the signal that existed in the signal cabling.